



**"Building a Better Brand"**

**L.H. Dottie Company**

6131 Garfield Avenue

Commerce, California 90040

**Call: 323-725-1000 • Fax: 323-721-0000**

## Item # 822, (822) Rubber Adhesive Tape

Rubber Tape is used in combination with friction and vinyl tape for primary insulation up to 600 volts and for use around split bolt connections, terminal lugs and compression connectors. It is used for insulating and waterproof applications, and easily conforms to irregular shapes and surfaces yielding a void free, electrically stable buildup. It is compatible with all extruded dielectric cable insulations.

3/4" x 22' Rubber Tape.



## Product Specifications | Packaging Specifications

### Product Specifications

|                        |              |
|------------------------|--------------|
| <b>Category Number</b> | 5370         |
| <b>UPC Code</b>        | 781002281207 |
| <b>Sort</b>            | 2436         |
| <b>Material</b>        | Rubber       |
| <b>Length</b>          | 22 ft.       |
| <b>Width</b>           | 3/4 in.      |

### Packaging Specifications

|                      |    |
|----------------------|----|
| <b>Unit Quantity</b> | 10 |
|----------------------|----|

|  |           |
|--|-----------|
| <b>Carton Quantity</b>   | 100       |
| <b>Unit (UM)</b>   | Each      |
| <b>Package Length</b>  | 4.00 in.  |
| <b>Package Width</b>   | 4 in.     |
| <b>Package Height</b>  | 0.60 in.  |
| <b>Package Weight</b>  | 0.350 lb. |
| <b>United Nations Standard Products &amp; Services Code (UNSPSC)</b> | 31201502  |